



# TBA Cane Toad 25




Oil Pattern Distance	47	Reverse Brush Drop	38	Oil Per Board	50 ul
Forward Oil Total	16.75 mL	Reverse Oil Total	10.1 mL	Volume Oil Total	26.85 mL
Tank Configuration	Multi Tank	Tank A Conditioner	ICE	Tank B Conditioner	ICE

	START	STOP	LOADS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	4	18	A	148	0.0	7.6	7.6	7400
2	8L	8R	4	18	B	100	7.6	17.8	10.2	5000
3	11L	11R	3	18	B	57	17.8	25.4	7.6	2850
4	13L	13R	2	22	B	30	25.4	31.6	6.2	1500
5	2L	2R	0	22	A	0	31.6	39.0	7.4	0
6	2L	2R	0	26	A	0	39.0	47.0	8.0	0

	START	STOP	LOADS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	26	A	0	47.0	33.0	-14.0	0
2	14L	14R	2	22	A	26	33.0	26.8	-6.2	1300
3	12L	12R	2	22	A	34	26.8	20.6	-6.2	1700
4	10L	10R	2	18	B	42	20.6	15.5	-5.1	2100
5	9L	9R	2	18	B	46	15.5	10.4	-5.1	2300
6	7L	7R	2	14	A	54	10.4	6.5	-3.9	2700
7	2L	2R	0	14	A	0	6.5	0.0	-6.5	0

Cleaner Ratio Main Mix NA Forward  
Cleaner Ratio Back End Mix NA Reverse  
Cleaner Ratio Back End Distance NA Combined  
Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	5.23	1.6	1.02	1.02	1.6	5.23

